



2022 TRX 766/766 i Series Specifications

	TRX 766 i Finish Cut Deck	TRX 766 i All-terrain Deck	TRX 766 Finish Cut Deck	TRX 766 All-terrain Deck
Engine	Engine	Briggs & Stratton Vanguard™ EFI	Briggs & Stratton Vanguard™ EFI	Kawasaki® FX
	Horsepower	37 hp	37 hp	35 hp
	Displacement	993 cc	993 cc	999 cc
	Cylinders	2	2	2
	Air Filter	5" Cyclonic	5" Cyclonic	5" Cyclonic
	Fuel	Gasoline	Gasoline	Gasoline
	Fuel Capacity	14 gallons	14 gallons	14 gallons
	Fuel Tank	Side, Double	Side, Double	Side, Double
Drive Line	Transmission Type	Hydrostatic	Hydrostatic	Hydrostatic
	Transmission	Hydro-Gear ZT-5400 Dual Range	Hydro-Gear ZT-5400 Dual Range	Hydro-Gear ZT-5400 Dual Range
	Max Forward Speed	11 mph	11 mph	11 mph
	Front Tire Size	15" Flat-Free Tires	15" Flat-Free Tires	15" Flat-Free Tires
	Rear Track Size	11" x 81" Track	11" x 81" Track	11" x 81" Track
Dimension/ Weight	Length	96"	96"	96"
	Width (Chute Up)	67.5"	67.5"	67.5"
	Height (ROPS Up)	79"	79"	79"
	Weight	1600 lbs	1600 lbs	1600 lbs
Cutting Deck	Cutting Width	66"	66"	66"
	Deck Construction	Fabricated Steel Aero Deck	Fabricated Steel HV All-Terrain Deck	Fabricated Steel Aero Deck
	Deck Thickness	Laminated 10 and 7 Gauge	Laminated 7 and 7 Gauge	Laminated 10 and 7 Gauge
	Deck Depth	5.5"	6"	5.5"
	Cut Height (Min - Max)	2.5" - 6"	3" - 7"	2.5" - 6"
	Cutting Height Steps	1/4" Increments	1/4" Increments	1/4" Increments
	Number of Blades	3	6 All-Terrain Blades	3
	Blade Speed	18,500 fpm	18,500 fpm	18,500 fpm
	Anti-Scalp Wheels	6 Recessed	n/a	6 Recessed
	Deck Lifting System	Manual	Manual	Manual
	Clutch Torque	250 ft-lbs	250 ft-lbs	250 ft-lbs
Clutch Manufacturer	Warner	Warner	Warner	
Warranty	Homeowner/ Commercial	3 Year Unlimited Engine 2 Year Unlimited Transmission 1 Year Manufacturer		
	Additional Features	TorqFlex™ Front Suspension 12-way Adjustable Suspension Seat SmarTrac™ Pro Display Soft Start Clutch Engagement	Keyless Push-to-Start Oil Warning Light No Slip Floor Mat Turf Track	



2022 TRX 354/561 Series Specifications

	TRX 354	TRX 561	
Engine	Engine	Kawasaki® FT	Kawasaki® FX
	Horsepower	24 hp	31 hp
	Displacement	726 cc	999 cc
	Cylinders	2	2
	Air Filter	Multi-Stage Canister	Multi-Stage Canister
	Fuel	Gasoline	Gasoline
	Fuel Capacity	10 gallons	14 gallons
	Fuel Tank	Side, Double	Side, Double
Drive Line	Transmission Type	Hydrostatic	Hydrostatic
	Transmission	Hydro-Gear ZT-3400	Hydro-Gear ZT-4400
	Max Forward Speed	8 mph	9 mph
	Front Tire Size	13" Flat-Free Tires	13" Flat-Free Tires
	Rear Track Size	11" x 71" Turf Track Standard	11" x 74" Turf
Dimension/ Weight	Length	84.5"	93"
	Width (Chute Up)	55"	62"
	Height (ROPS Up)	76"	79"
	Weight	1220 lbs	1540 lbs
Cutting Deck	Cutting Width	54"	61"
	Deck Construction	Fabricated Steel Aero Deck	Fabricated Steel Aero Deck
	Deck Thickness	Laminated 10 and 10 Gauge	Laminated 10 and 7 Gauge
	Deck Depth	4.5"	5.5"
	Cut Height (Min - Max)	2.25" - 5"	2.5" - 6"
	Cutting Height Steps	1/4" Increments	1/4" Increments
	Number of Blades	3	3
	Blade Speed	18,500 fpm	18,500 fpm
	Anti-Scalp Wheels	5 Recessed	6 Recessed
	Deck Lifting System	Manual	Manual
	Clutch Torque	200 ft-lbs	250 ft-lbs
	Clutch Manufacturer	Warner	Warner
	Warranty	Homeowner/ Commercial 3 Year Unlimited Engine 2 Year Unlimited Transmission 1 Year Manufacturer	
Additional Features	TorqFlex™ Front Suspension*	Oil Warning Light*	
	12-way Adjustable Suspension Seat SmarTrac™ Pro Display* Soft Start Clutch Engagement* Keyless Push-to-Start*	No Slip Floor Mat Turf Tracks* Rear Hitch installed on TRX 354 models	

*TRX 561 models only.

Optional Independent Front Suspension available for TRX 354 models.